

BRAKECON

BRAKE FLUIDS

BRAKE FLUID DOT 4



BRAKECON RANGE

6 products · 3 grades

DOT 3	1	DOT 4	3
DOT 5.1	1		

SPECIFICATIONS · DOT 4

- FMVSS 116 DOT 4
- ISO 4925 CLASS 4
- JIS K2233 CLASS 4
- SFU IVECO 18-1820
- SFU
- RENAULT RN 41-02-001/E
- SFU NISSAN NES-M5055
- FIAT FCA9.55597-DOT4

Synthetic DOT 4 Brake Fluid for Disc and Drum Brakes, ABS and Hydraulic Clutches

Synthetic DOT 4 brake fluid based on polyglycol ethers, for compatible hydraulic braking systems with disc or drum brakes. It is intended for applications requiring DOT 4, including suitable ABS systems and hydraulic clutches, in accordance with the manufacturer's instructions.

KEY ADVANTAGES

- Low viscosity
- High resistance to vapour lock, caused by vapour bubbles that impair braking
- Low hygroscopic index
- Protection of the entire circuit from corrosion
- High resistance to oxidation

PACK	CODE	UNITS / BOX	PER PALLET
500 ml	GDEK601500	—	—
1 L	GDEK60101	18	54 boxes
20 L	GDEK60120	—	48 units
60 L	GDEK60160	—	18 units

BRAKECON

BRAKE FLUIDS

BRAKE FLUID DOT 4

TYPICAL CHARACTERISTICS

Property	Unit	Method	Typical value
Colour	-	Visual	Amber yellow
Appearance	-	Visual	Clear transparent
Density at 20°C	kg/m ³	ASTM D1298	1040
Kinematic viscosity at 100°C	cSt	ASTM D445	2
Kinematic viscosity at -20°C	cSt	ASTM D445	<1500
Dry boiling point	°C	ASTM D1120	>230
Water content (H2O)	%	ASTM E1064	0,001

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.