

POLARON COOLANTS & ANTIFREEZE

CRYSTA 100 G11 BLUE IAT



POLARON RANGE

19 products · 5 grades

G11	6	G12	3
G12+	2	G12++	3
G13	3		

SPECIFICATIONS · G11

- Technology: IAT
- CUNA NC 956-16 (I) VW G-11
- BS 6580 (GB) FVV Heft R 443 (D) Afnor R 15/601 (F) ASTM D 3306 and 4985 JIS K 2234 (J) KSM 2142 (K) NATO S 759 UNE 26361-88 (E) EMPA (CH) E/L 1415c (MIL Italy)
- CUMMINS CES 14603
- Porsche / VW/Audi/Seat/Skoda TL 774 C G11
- Mercedes DBL 7700
- FIAT 9.55523/41

Concentrated IAT Monoethylene Glycol Antifreeze for Older Cast Iron & Ferrous Engines

Concentrated monoethylene glycol antifreeze, specifically for cooling circuits of older engines requiring IAT, with bodies made of cast iron, iron, steel and ferrous metals.

KEY ADVANTAGES

- Maximum protection of engine circuits with cast iron and ferrous components
- High heat dissipation capacity
- Tracer to quickly detect leaks in the circuit
- Excellent protection of the water pump and all rubber parts
- Raised boiling point

PACK	CODE	UNITS / BOX	PER PALLET
1 L	GDEK92501	18	54 boxes
5 L	GDEK92505	4	50 boxes
20 L	GDEK92520	—	48 units
60 L	GDEK92560	—	18 units
208 L	GDEK925208	—	4 units
1.000 L	GDEK9251000	—	1 unit

POLARON COOLANTS & ANTIFREEZE

CRYSTA 100 G11 BLUE IAT

TYPICAL CHARACTERISTICS

Property	Unit	Method	Typical value
Colour	-	ASTM D3306	Turquoise/blue
Appearance	-	ASTM D3306	Limpid
Density	kg/dm ³	ASTM D3306	1,12
pH (50% dilution)	-	ASTM D3306	8,9
Boiling point	°C	ASTM D1120	197
Freezing point (50% dilution)	°C	ASTM D1177	-38
Glass corrosion test	mg/specimen	ASTM D1384	Pass

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.