

POLARON COOLANTS & ANTIFREEZE

CRYSTA 100 G11 GREEN IAT



POLARON RANGE

19 products · 5 grades

G11	6	G12	3
G12+	2	G12++	3
G13	3		

SPECIFICATIONS · G11

- Technology: IAT
- CUNA 956-16 VW G11 BS 6580
- VW TL 774-C
- MB 325.0 -
- MB 325.2 - MB DBL 7700-00 E/L
- VOLVO 1286083
- MAN 324 NF AFNOR R15-601
- MTU MTL 5048 NATO S-759/ NATO S-750
- OPEL /
- GM B0400240 / QL130100 /
- OPEL GME L 1301 /
- GM US 6277-M
- RENAULT 41-01-001 TYPE C SAAB 6901599
- SCANIA TB 1451 002/132
- FIAT 9.55523 IVECO 18-1830
- BMW N 600 69.0
- CHRYSLER MS 7170 FF.SS.
- CAT

Concentrated IAT Monoethylene Glycol Antifreeze for Older Cast Iron & Ferrous Engines

Concentrated monoethylene glycol antifreeze for cooling circuits of older engines requiring IAT, such as engines with bodies made of cast iron, iron, steel and ferrous metals.

KEY ADVANTAGES

- Maximum protection of engine circuits with cast iron and ferrous components
- High heat dissipation capacity
- Tracer to quickly detect leaks in the circuit
- Excellent protection of the water pump and all rubber parts
- Raised boiling point

PACK	CODE	UNITS / BOX	PER PALLET
1 L	GDEK90801	18	54 boxes
5 L	GDEK90805	4	50 boxes
20 L	GDEK90820	—	48 units
60 L	GDEK90860	—	18 units
208 L	GDEK908208	—	4 units
1.000 L	GDEK9081000	—	1 unit

POLARON COOLANTS & ANTIFREEZE

CRYSTA 100 G11 GREEN IAT

TYPICAL CHARACTERISTICS

Property	Unit	Method	Typical value
Colour	-	ASTM D3306	Green
Appearance	-	ASTM D3306	Limpid
Density	kg/dm ³	ASTM D3306	1,11
pH (50% dilution)	-	ASTM D3306	8,8
Boiling point	°C	ASTM D1120	196
Freezing point (50% dilution)	°C	ASTM D1177	-36
Glass corrosion test	mg/specimen	ASTM D1384	Pass

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.