

POLARON COOLANTS & ANTIFREEZE

CRYSTA 20 G12 RED OAT



POLARON RANGE

19 products · 5 grades

G11	6	G12	3
G12+	2	G12++	3
G13	3		

SPECIFICATIONS · G12

- Technology: OAT
- BS 6580 AFNOR R15-601 ASTM D 3306/D4985
- PORSCHE / VW / AUDI / SEAT / SKODA TL 774C
- FORD FSD M97 B49-A
- GM US 6277M
- FORD ESD M97 B49-A
- CHRYSLER MS 9176
- Exceeds the ASTM methods that assess protective properties
- Glassware corrosion: ASTM D1384
- Dynamic corrosion: CUNA/MA/SC55 GdL 1
- Elastomer compatibility: CUNA NC 903-07
- Ultrasonic cavitation erosion: ASTM D2966
- Hot-surface aluminium corrosion: ASTM D4340

Ready-to-Use OAT Antifreeze for Aluminium-Alloy and Light-Metal Engines

Ready-to-use monoethylene glycol antifreeze with OAT technology. For cooling circuits of internal combustion engines made of aluminium alloys and light metals.

KEY ADVANTAGES

- Good protection of aluminium-alloy engine circuits
- High heat dissipation capacity
- Tracer to quickly detect leaks in the circuit
- NAP-free (nitrate, amine and phosphate free)

PACK	CODE	UNITS / BOX	PER PALLET
1 L	GDEK90501	18	54 boxes
4 L	GDEK90544	4	60 boxes
20 L	GDEK90520	—	48 units
60 L	GDEK90560	—	18 units
208 L	GDEK905208	—	4 units
1.000 L	GDEK9051000	—	1 unit

POLARON COOLANTS & ANTIFREEZE

CRYSTA 20 G12 RED OAT

TYPICAL CHARACTERISTICS

Property	Unit	Method	Typical value
Colour	-	ASTM D3306	Red
Appearance	-	ASTM D3306	Limpid
Density	kg/dm ³	ASTM D3306	1,04
pH (diluted)	-	ASTM D3306	8,4
Boiling point	°C	ASTM D1120	106
Freezing Point	°C	ASTM D1177	-20
Glass corrosion test	mg/specimen	ASTM D1384	Pass

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.