

AUTRON

AUTOMATIC TRANSMISSION FLUIDS

DRIVON ATF IIIH



AUTRON RANGE

8 products · Automatic Transmission Fluids

SPECIFICATIONS

- GM DEXRON III ZF TE-ML 03D /05L/21L/ML-09/ML-04D/1A/ML 17C
- VOLVO CE 97341 M,B236.9
- MB 236.1
- MAN 339 V-1 /TYPE Z2 Z3
- ALLISON TES-389MB-Approval 236.6 Voith H55.6335.xx

Synthetic Dexron IIIH Fluid for Automatic Transmissions & Torque Converters

Synthetic high viscosity index fluid for compatible multi-speed automatic gearboxes, torque converters and hydraulic transmissions requiring Dexron IIIH level. Its use in power steering or selected manual gearboxes requires the relevant manufacturer instruction.

KEY ADVANTAGES

- Very high thermal and oxidative stability
- Exceptional friction control
- Maximum resistance to wear
- Maximum compatibility with materials used in these systems
- Immediate control response even at low temperatures

PACK	CODE	UNITS / BOX	PER PALLET
1 L	GDEK50101	18	54 boxes
4 L	GDEK50144	4	60 boxes
20 L	GDEK50120	—	48 units
60 L	GDEK50160	—	18 units

AUTRON

AUTOMATIC TRANSMISSION FLUIDS

DRIVON ATF IIIH

TYPICAL CHARACTERISTICS

Property	Unit	Method	Typical value
Colour	-	Visual	Red
Appearance	-	Visual	Limpid
Density	kg/dm ³	ASTM D7042	0,852
Kinematic viscosity at 40°C	cSt	ASTM D445	33
Kinematic viscosity at 100°C	cSt	ASTM D445	7,5
Viscosity Index	-	ASTM D2270	190
Flash Point	°C	ASTM D92	222
Pour Point	°C	ASTM D97	-44

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.