

MAXTOR TRUCKS & HEAVY DUTY

FERON 15W-40 CK-4



MAXTOR RANGE

14 products · 8 grades

SAE 0W-20	1	SAE 5W-20	1
SAE 5W-30	3	SAE 5W-40	1
SAE 10W-30	1	SAE 10W-40	2
SAE 15W-40	4	SAE 20W-50	1

SPECIFICATIONS · SAE 15W-40

- API CK-4/ CJ-4/CI-4+/CI-4/CH-4
- ACEA E11/E9/E8/E6/E4
- DTFR 15C100 (MB 228.31)
- DETROIT 93 K222
- CATERPILLAR ECF-3
- FORD WSS M2C171-E
- FORD WSS M2C171-F
- MAN 3775
- VOLVO VDS-4.5
- MACK EO-O-PREMIUM PLUS
- MACK EOS 4.5
- RENAULT RVI RLD-3 / RLD-4
- CUMMINS CES20086
- DEUTZ DQC III-18 LA
- MTU
- CAT Type 2.1

SAE 15W-40 Lubricant for Naturally Aspirated & Turbo Diesel Engines with EGR and DPF

For naturally aspirated and turbocharged diesel engines with EGR, DPF where fitted, and NOx reduction. The formulation is linked to E11 requirements and low-sulphur fuels.

KEY ADVANTAGES

- Effective prevention of deposits, varnishes and sludge
- Maximum thermal stability
- Maximum detergency
- High dispersancy, anticorrosion and antirust properties

PACK	CODE	UNITS / BOX	PER PALLET
5 L	GDEK20605	4	50 boxes
20 L	GDEK20620	—	48 units
60 L	GDEK20660	—	18 units
208 L	GDEK206208	—	4 units
1.000 L	GDEK2061000	—	1 unit

MAXTOR TRUCKS & HEAVY DUTY

FERON 15W-40 CK-4

TYPICAL CHARACTERISTICS

Property	Unit	Method	Typical value
Colour	-	Visual	Amber
Appearance	-	Visual	Limpid
Density	kg/dm ³	ASTM D7042	0,87
Kinematic viscosity at 40°C	cSt	ASTM D445	99,5
Kinematic viscosity at 100°C	cSt	ASTM D445	14,5
Viscosity Index	-	ASTM D2270	151
Flash Point	°C	ASTM D92	233
Pour Point	°C	ASTM D97	-26

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.