

GEARTRON

GEAR OILS

FERON 85W-90 AXLE EP



GEARTRON RANGE

9 products · 6 grades

SAE 75W	1	SAE 75W-80	2
SAE 75W-90	2	SAE 75W-140	1
SAE 80W-90	2	SAE 85W-90	1

SPECIFICATIONS · SAE 85W-90

- API GL-5 MT -1
- MIL - L 2105 C/D SAE J-2360
- DTFR 12B100
- MB 235.0
- ARVINMERITOR 076-A
- SCANIA ST01:0
- MAN342 TYPE M2
- ZF TE-ML 05A/12E/16B/17B/19B/21A

Mineral EP Gear Lubricant for Axles, Reduction Gears & Hypoid Differentials

SAE 85W-90 lubricant with hydroisomerized mineral bases and extreme pressure (EP) additives for axles, reduction gears and hypoid differentials. Intended for mechanisms requiring API GL-5, with emphasis on gear protection under load.

KEY ADVANTAGES

- Maximum protection of gears against wear thanks to extreme pressure performance
- Exceptional friction control
- Maximum compatibility with materials used in these systems
- Low pour point
- High anti-corrosion and anti-rust properties

PACK	CODE	UNITS / BOX	PER PALLET
1 L	GDEK51801	18	54 boxes
4 L	GDEK51844	4	60 boxes
20 L	GDEK51820	—	48 units
60 L	GDEK51860	—	18 units
208 L	GDEK518208	—	4 units

GEARTRON

GEAR OILS

FERON 85W-90 AXLE EP

TYPICAL CHARACTERISTICS

Property	Unit	Method	Typical value
Colour	-	Visual	Amber
Appearance	-	Visual	Limpid
Density	kg/dm ³	ASTM D7042	0,880
Kinematic viscosity at 40°C	cSt	ASTM D445	130
Kinematic viscosity at 100°C	cSt	ASTM D445	15
Viscosity Index	-	ASTM D2270	118
Flash Point	°C	ASTM D92	241
Pour Point	°C	ASTM D97	-29

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.