

MAXTOR TRUCKS & HEAVY DUTY

FORTIS 20W-50 CI-4



MAXTOR RANGE

14 products · 8 grades

SAE 0W-20	1	SAE 5W-20	1
SAE 5W-30	3	SAE 5W-40	1
SAE 10W-30	1	SAE 10W-40	2
SAE 15W-40	4	SAE 20W-50	1

SPECIFICATIONS · SAE 20W-50

- API CI-4
- ACEA E7
- DTFR 15B110 (228.3)
- JASO DH-1

Full SAPS Multigrade Lubricant for Turbocharged Heavy-Duty Diesel Engines

Multigrade SAE 20W-50 Full SAPS lubricant for selected turbocharged heavy-duty diesel engines. Intended for compatible transport and earthmoving machinery applications with increased load requirements, when the manufacturer specifies SAE 20W-50.

KEY ADVANTAGES

- Maximum oxidative stability
- Prevention of deposits, varnishes and sludge
- Maximum thermal stability
- Maximum detergency
- High dispersancy, anticorrosion and antirust properties

PACK	CODE	UNITS / BOX	PER PALLET
5 L	GDEK20805	4	50 boxes
20 L	GDEK20820	—	48 units
60 L	GDEK20860	—	18 units
208 L	GDEK208208	—	4 units
1.000 L	GDEK2081000	—	1 unit

MAXTOR TRUCKS & HEAVY DUTY

FORTIS 20W-50 CI-4

TYPICAL CHARACTERISTICS

Property	Unit	Method	Typical value
Colour	-	Visual	Amber
Appearance	-	Visual	Limpid
Density	kg/dm ³	ASTM D7042	0,868
Kinematic viscosity at 40°C	cSt	ASTM D445	148
Kinematic viscosity at 100°C	cSt	ASTM D445	19,6
Viscosity Index	-	ASTM D2270	152
Flash Point	°C	ASTM D92	232
Pour Point	°C	ASTM D97	-24

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.