

AGRONOX

AGRICULTURE & OFF-HIGHWAY

GEARFORCE 80W-90 AXLE EP

AGRONOX

SAE 80W-90



AGRONOX RANGE

25 products · 16 grades

SAE 5W-30	1	SAE 10W	2
SAE 10W-30	2	SAE 10W-40	2
SAE 15W-40	2	SAE 20W-30	1
SAE 20W-50	1	SAE 75W-90	1
SAE 80W	1	SAE 80W-90	1
SAE 85W-140	1	SAE 30	2
SAE 40	2	SAE 90	1
SAE 140	1	SAE 250	1

SPECIFICATIONS · SAE 80W-90

- API GL 5 MT -1 GL4
- MIL - L 2105 C/D SAE J-2360
- ARVINMERITOR 076-A
- SCANIA ST01:0 ST0 1:1G
- MAN342 TYPE M2/M3
- MAN 341 TYPE GA1/Z-2
- SFU IVECO RAM-1
- RENAULT TRUCK
- VOLVO 97321 DAF-90
- ZF TE-ML
05A/12E/16B/17B/19B/21A

GL-5 EP Gear Lubricant for Hypoid Differentials & Heavily Loaded Axles

SAE 80W-90 GL-5 lubricant with extreme pressure (EP) additives, for compatible hypoid differentials, reduction gears and heavily loaded axles of commercial and agricultural equipment. Not automatically recommended for GL-4 synchronized gearboxes.

KEY ADVANTAGES

- Maximum protection of gears against wear thanks to extreme pressure performance
- Exceptional friction control
- Maximum compatibility with materials used in these systems
- Low pour point
- High anti-corrosion and anti-rust properties

PACK	CODE	UNITS / BOX	PER PALLET
5 L	GDEK51305	4	50 boxes
20 L	GDEK51320	—	48 units
208 L	GDEK513108	—	4 units
1.000 L	GDEK5131000	—	1 unit

AGRONOX

AGRICULTURE & OFF-HIGHWAY

GEARFORCE 80W-90 AXLE EP

TYPICAL CHARACTERISTICS

Property	Unit	Method	Typical value
Colour	-	Visual	Amber
Appearance	-	Visual	Limpid
Density	kg/dm ³	ASTM D7042	0,891
Kinematic viscosity at 40°C	cSt	ASTM D445	125
Kinematic viscosity at 100°C	cSt	ASTM D445	14,5
Viscosity Index	-	ASTM D2270	118
Flash Point	°C	ASTM D92	241
Pour Point	°C	ASTM D97	-29
FZG scuffing test A/8,3/90	-	ISO 14635-1	12+

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.