

AGRONOX

AGRICULTURE & OFF-HIGHWAY

HARVEX 10W-40 CK-4



AGRONOX RANGE

25 products · 16 grades

SAE 5W-30	1	SAE 10W	2
SAE 10W-30	2	SAE 10W-40	2
SAE 15W-40	2	SAE 20W-30	1
SAE 20W-50	1	SAE 75W-90	1
SAE 80W	1	SAE 80W-90	1
SAE 85W-140	1	SAE 30	2
SAE 40	2	SAE 90	1
SAE 140	1	SAE 250	1

SPECIFICATIONS · SAE 10W-40

- API CK-4/ CJ-4/CI-4+/CI-4/CH-4
- ACEA E11/E9/E8/E6/E4
- DTFR 15C100 (MB 228.31), DTFR 15C110 (MB 228.51), DTFR 15C120 (MB 228.52)
- DETROIT 93 K222 SFU IVECO 18-1804 TLS CK4
- CATERPILLAR ECF-3
- SCANIA LA
- MAN 3271-1/3477/3775
- VOLVO VDS-4.5
- VOLVO CNG
- MACK EOS 4.5
- RENAULT RVI RLD-3 / RLD-4
- CUMMINS CES 20081/ CES20086
- JASO DH-2
- DEUTZ DQC III-10-LA/DQC IV-18-LA
- MTU
- CAT Type 2.1/3.1

Low SAPS Synthetic-Based Lubricant for Truck & Professional Diesel Engines

SAE 10W-40 lubricant with Low SAPS technology for compatible heavy-duty vehicle and commercial machinery diesel engines. The reduced ash-forming content supports applications with suitable exhaust aftertreatment systems, always in accordance with the required engine specification.

KEY ADVANTAGES

- Low friction for better protection
- Counteraction against the molecular oxidation of the lubricant
- Maximum thermal stability
- Maximum detergency
- High dispersancy, anticorrosion and antirust properties

PACK	CODE	UNITS / BOX	PER PALLET
5 L	GDEK20405	4	50 boxes
20 L	GDEK20420	—	48 units
208 L	GDEK204208	—	4 units
1.000 L	GDEK2041000	—	1 unit

AGRONOX AGRICULTURE & OFF-HIGHWAY

HARVEX 10W-40 CK-4

TYPICAL CHARACTERISTICS

Property	Unit	Method	Typical value
Colour	-	Visual	Amber
Appearance	-	Visual	Limpid
Density	kg/dm ³	ASTM D7042	0,862
Kinematic viscosity at 40°C	cSt	ASTM D445	92,5
Kinematic viscosity at 100°C	cSt	ASTM D445	14,5
Viscosity Index	-	ASTM D2270	163
Flash Point	°C	ASTM D92	232
Pour Point	°C	ASTM D97	-31

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.