

AGRONOX AGRICULTURE & OFF-HIGHWAY

HARVEX 15W-40 POWER



AGRONOX RANGE

25 products · 16 grades

SAE 5W-30	1	SAE 10W	2
SAE 10W-30	2	SAE 10W-40	2
SAE 15W-40	2	SAE 20W-30	1
SAE 20W-50	1	SAE 75W-90	1
SAE 80W	1	SAE 80W-90	1
SAE 85W-140	1	SAE 30	2
SAE 40	2	SAE 90	1
SAE 140	1	SAE 250	1

SPECIFICATIONS · SAE 15W-40

- API CJ-4/CI-4+/CI-4/CH-4
- ACEA E7/E5
- DTFR 15B120 (MB 228.5) DTFR 15B110 (228.3)
- MAN 3275-1 CATERPILLAR ECF-2 / ECF-A
- MTU Type 3 - OIL TYPE 2 Deutz DQC IV-10
- CUMMINS CES 20078 JASO FH-1
- VOLVO VDS-3
- RENAULT RVI RLD-2
- Mack EO-N / EO-M / EO-M PLUS
- SFU IVECO DH-1 18-1804 T2 E7

Full SAPS Lubricant for Turbocharged Heavy-Duty Diesel Engines

SAE 15W-40 lubricant for compatible turbocharged or naturally aspirated diesel engines of commercial and off-road equipment. Intended for demanding operating and load conditions in which this viscosity level and performance level are specified.

KEY ADVANTAGES

- Maximum oxidative stability
- Prevention of deposits, varnishes and sludge
- Maximum thermal stability
- Maximum detergency
- High dispersancy, anticorrosion and antirust properties

PACK	CODE	UNITS / BOX	PER PALLET
5 L	GDEK20705	4	50 boxes
20 L	GDEK20720	—	48 units
208 L	GDEK207208	—	4 units
1.000 L	GDEK2071000	—	1 unit

AGRONOX AGRICULTURE & OFF-HIGHWAY

HARVEX 15W-40 POWER

TYPICAL CHARACTERISTICS

Property	Unit	Method	Typical value
Colour	-	Visual	Amber
Appearance	-	Visual	Limpid
Density	kg/dm ³	ASTM D7042	0,865
Kinematic viscosity at 40°C	cSt	ASTM D445	101
Kinematic viscosity at 100°C	cSt	ASTM D445	14,7
Viscosity Index	-	ASTM D2270	151
Flash Point	°C	ASTM D92	233
Pour Point	°C	ASTM D97	-26

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.