

AGRONOX

AGRICULTURE & OFF-HIGHWAY

HARVEX 5W-30 CK-4



AGRONOX RANGE

25 products · 16 grades

SAE 5W-30	1	SAE 10W	2
SAE 10W-30	2	SAE 10W-40	2
SAE 15W-40	2	SAE 20W-30	1
SAE 20W-50	1	SAE 75W-90	1
SAE 80W	1	SAE 80W-90	1
SAE 85W-140	1	SAE 30	2
SAE 40	2	SAE 90	1
SAE 140	1	SAE 250	1

SPECIFICATIONS · SAE 5W-30

- API CK4/CJ-4/CI-4+/CI-4/CH-4
- ACEA E11/E9/E7/E6/E4
- DAIMLER TRUCK DTFR 15C120 (MB 228.52)
- DTFR 15C110 (MB 228.51) DTFR 15C100 (MB 228.31)
- MAN 3477 M3777 M3775 M3677 M3691 M3271-1 MTU3.1
- VOLVO VDS-5 VDS-4.5/VDS 3/CNG
- RENAULT RLD-3 RLD-4
- SCANIA LA and LDF-4 JASO DH-2 DH-1 DL 0
- SFU IVECO 18-1811 IVECO 18-1804 TLS-E6 IVECO 18-1804 TLS-E9
- CUMMINS CES20086 CES 20081
- DEUTZ DQC IV-10 LA/ DQC IV-18 LA DETROIT DIESEL 93K218 CATERPILLAR ECF-3
- MACK EO-O PREMIUM PLUS
- MACK EOS 4.5

Low SAPS Synthetic-Based Lubricant for Heavy-Duty Diesel Engines with After-Treatment

Synthetic-based SAE 5W-30 lubricant with Low SAPS technology for compatible diesel engines of commercial and heavy-duty vehicles. The controlled content of ash, phosphorus and sulphur makes it suitable for applications with exhaust aftertreatment systems, such as DPF and SCR, provided the manufacturer so specifies.

KEY ADVANTAGES

- Prevention of molecular oxidation of the lubricant
- Maximum thermal stability
- Maximum detergency
- High dispersancy, anticorrosion and antirust properties

PACK	CODE	UNITS / BOX	PER PALLET
5 L	GDEK20105	4	50 boxes
20 L	GDEK20120	—	48 units
208 L	GDEK201208	—	4 units
1.000 L	GDEK2011000	—	1 unit

AGRONOX AGRICULTURE & OFF-HIGHWAY

HARVEX 5W-30 CK-4

TYPICAL CHARACTERISTICS

Property	Unit	Method	Typical value
Colour	-	Visual	Amber
Appearance	-	Visual	Limpid
Density	kg/dm ³	ASTM D7042	0,859
Kinematic viscosity at 40°C	cSt	ASTM D445	61,8
Kinematic viscosity at 100°C	cSt	ASTM D445	10,6
Viscosity Index	-	ASTM D2270	163
Flash Point	°C	ASTM D92	229
Pour Point	°C	ASTM D97	-36

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.