

BRAKECON

BRAKE FLUIDS

LHM HYDRAULIC FLUID



BRAKECON RANGE

6 products - 3 grades

DOT 3	1	DOT 4	3
DOT 5.1	1		

SPECIFICATIONS

- PSA PEUGEOT CITROEN B71 2710
- FORD ESN M6C 59A ISO 7308
- MASSEY FERGUSON MF
- VW 2000

Mineral LHM Hydraulic Fluid for Central Brake, Suspension and Steering Systems

Special LHM mineral hydraulic fluid for compatible central hydraulic systems of vehicles that combine braking, hydropneumatic suspension and hydraulic power steering functions. It may also be used in special clutch control circuits, only where LHM is specified by the manufacturer. It is not a substitute for polyglycol-based DOT brake fluids.

KEY ADVANTAGES

- Maximum detergency
- Excellent oxidation stability
- Low pour point and very high viscosity index for protection even with strong temperature changes
- Excellent anti-wear performance for all metals and alloys, reducing friction and energy absorption

PACK	CODE	UNITS / BOX	PER PALLET
500 ml	GDEK604500	—	—
1 L	GDEK60401	18	54 boxes
20 L	GDEK60420	—	48 units
60 L	GDEK60460	—	18 units

BRAKECON

BRAKE FLUIDS

LHM HYDRAULIC FLUID

TYPICAL CHARACTERISTICS

Property	Unit	Method	Typical value
Colour	-	Visual	Green
Appearance	-	Visual	Limpid
Density	kg/dm ³	ASTM D7042	0,845
Kinematic viscosity at -40°C	cSt	ASTM D445	1400
Flash Point	°C	ASTM D92	226
Freezing Point	°C	ASTM D97	-52

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.