

AGRONOX AGRICULTURE & OFF-HIGHWAY

PTFORZA 80W UTTO



AGRONOX RANGE

25 products · 16 grades

SAE 5W-30	1	SAE 10W	2
SAE 10W-30	2	SAE 10W-40	2
SAE 15W-40	2	SAE 20W-30	1
SAE 20W-50	1	SAE 75W-90	1
SAE 80W	1	SAE 80W-90	1
SAE 85W-140	1	SAE 30	2
SAE 40	2	SAE 90	1
SAE 140	1	SAE 250	1

SPECIFICATIONS · SAE 80W

- API GL-4
- ALLISON C-4 TES -439
- Caterpillar TO-4 / TO-4M / TO-2
- JOHN DEERE J20A / J20B / J20C / J20D
- ZF TEML 03 E / 03 C / 05 E / 05 F / 06 E / 07D / 07F / 17 E / 21 F
- CNH MAT 3505, 3525, 3540
- FORD M2C86B
- FORD ESN -M2C-134D
- FORD ESN M2C-134JD
- VOLVO VCE VME WB 101
- DENINSON HFO
- Massey Ferguson : M1145 M1143 M1135 KUBOTA UDT FLUID
- VALTRA G2 G2-B10
- VICKERS EATON I-280 DANFOS
- NEW HOLLAND 82948718
- KOMATSU DRESSER B-06 0001-0002

UTTO Fluid for Agricultural Transmissions & Hydraulic Mechanisms

UTTO type SAE 80W fluid for compatible agricultural transmissions and hydraulic mechanisms. Intended for applications where the manufacturer specifies common lubrication of gearbox, hydraulics and, as applicable, wet brakes.

KEY ADVANTAGES

- Protection against the molecular oxidation of the lubricant
- Maximum thermal stability
- Superior cleaning power
- Excellent dispersing, anti-corrosion and anti-rust properties

PACK	CODE	UNITS / BOX	PER PALLET
5 L	GDEK30905L	4	50 boxes
20 L	GDEK30920L	—	48 units
208 L	GDEK309208L	—	4 units
1.000 L	GDEK3091000L	—	1 unit

AGRONOX AGRICULTURE & OFF-HIGHWAY

PTFORZA 80W UTTO

TYPICAL CHARACTERISTICS

Property	Unit	Method	Typical value
Colour	-	Visual	Amber
Appearance	-	Visual	Limpid
Density	kg/dm ³	ASTM D7042	0,87
Kinematic viscosity at 40°C	cSt	ASTM D445	62
Kinematic viscosity at 100°C	cSt	ASTM D445	9,9
Viscosity Index	-	ASTM D2270	145
Flash Point	°C	ASTM D92	232
Pour Point	°C	ASTM D97	-43

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.