

MOTRONIX

MOTORCYCLES

RACETRON 10W-50 4T



MOTRONIX RANGE

19 products · 13 grades

SAE 5W	1	SAE 5W-40	2
SAE 5W-50	1	SAE 10W	1
SAE 10W-40	2	SAE 10W-50	2
SAE 10W-60	1	SAE 15W	1
SAE 15W-40	1	SAE 15W-50	1
SAE 15W-60	1	SAE 20W-40	1
SAE 20W-50	1		

SPECIFICATIONS · SAE 10W-50

- API SP/ SN/SM
- JASO T903 JASO MA-MA2
- JASO Quality Category SP

Four-Stroke Motorcycle Engine Oil SAE 10W-50 for Road Bikes & Recreational Vehicles

SAE 10W-50 lubricant for four-stroke road motorcycle engines and selected ATV, SXS or other recreational vehicle applications where this category is specified. Designed for demanding operating conditions. Wet clutch suitability and the JASO specification must be consistent with the manual and the current TDS.

KEY ADVANTAGES

- Maximum heat dissipation
- Excellent oxidation stability
- High resistance to pre-ignition
- Low pour point and very high viscosity index, ensuring maximum protection even with extreme temperature fluctuations
- High detergent, anti-corrosion and anti-rust properties

PACK	CODE	UNITS / BOX	PER PALLET
1 L	GDEK40501	18	54 boxes
4 L	GDEK40544	4	60 boxes
20 L	GDEK40520	—	48 units
60 L	GDEK405060	—	18 units
208 L	GDEK4050208	—	4 units
1.000 L	GDEK40501000	—	1 unit

MOTRONIX

MOTORCYCLES

RACETRON 10W-50 4T

TYPICAL CHARACTERISTICS

Property	Unit	Method	Typical value
Colour	-	Visual	Amber
Appearance	-	Visual	Limpid
Density	kg/dm ³	ASTM D7042	0,862
Kinematic viscosity at 40°C	cSt	ASTM D445	20,5
Kinematic viscosity at 100°C	cSt	ASTM D445	157
Viscosity index	-	ASTM D2270	153
Flash Point	°C	ASTM D92	231
Pour point	°C	ASTM D97	-29

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.