

AGRONOX

AGRICULTURE & OFF-HIGHWAY

STOUVERA 10W-40 STOU



AGRONOX RANGE

25 products · 16 grades

SAE 5W-30	1	SAE 10W	2
SAE 10W-30	2	SAE 10W-40	2
SAE 15W-40	2	SAE 20W-30	1
SAE 20W-50	1	SAE 75W-90	1
SAE 80W	1	SAE 80W-90	1
SAE 85W-140	1	SAE 30	2
SAE 40	2	SAE 90	1
SAE 140	1	SAE 250	1

SPECIFICATIONS · SAE 10W-40

- API GL-3/GL-4/GL-5
- API CG-4/CF-4/CI-4
- ACEA E7/E4
- ZF TE-ML
- 03D/04D/6A/6B/6C/6F/6L/11B/14A/17C
- FORD M2C159B/C
- MASSEY FERGUSON M1139/M1145
- CNH MAT 3505/3509/3525/3526
- CATERPILLAR TO-2
- ALLISON C-4
- JOHN DEERE J20C/J20D
- MAN M3275
- EATON M2950S/I-280-S
- AFNOR NFE 48603
- DIN 51524-3 HVLP

Low-Friction Multifunctional STOU Lubricant for Agricultural Engines & Transmissions

STOU SAE 10W-40 multifunctional lubricant for agricultural engines and selected transmission or hydraulic applications. The manufacturer's FUEL ECONOMY designation points to a low-friction design, without documenting a specific percentage of fuel saving.

KEY ADVANTAGES

- Optimised friction
- Prevention of molecular oxidation of the lubricant
- TBN reserve for effective resistance to the formation of corrosive acids
- Maximum thermal stability
- Superior cleaning power
- Exceptional dispersing, anti-corrosion and anti-rust properties

PACK	CODE	UNITS / BOX	PER PALLET
5 L	GDEK31205	4	50 boxes
20 L	GDEK31220	—	48 units
208 L	GDEK312208	—	4 units
1.000 L	GDEK3121000	—	1 unit

AGRONOX AGRICULTURE & OFF-HIGHWAY

STOUVERA 10W-40 STOU

TYPICAL CHARACTERISTICS

Property	Unit	Method	Typical value
Colour	-	Visual	Amber
Appearance	-	Visual	Limpid
Density	kg/dm ³	ASTM D7042	0,87
Kinematic viscosity at 40°C	cSt	ASTM D445	84
Kinematic viscosity at 100°C	cSt	ASTM D445	14,6
Viscosity Index	-	ASTM D2270	138
Flash Point	°C	ASTM D92	228
Pour Point	°C	ASTM D97	-40

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.