

ZENTROX

PASSENGER CARS & VANS

TURION 5W-40 C3



ZENTROX RANGE

34 products · 16 grades

SAE 0W-16	1	SAE 0W-20	2
SAE 0W-30	4	SAE 0W-40	1
SAE 5W-20	2	SAE 5W-30	9
SAE 5W-40	4	SAE 10W-30	1
SAE 10W-40	3	SAE 10W-60	1
SAE 15W-40	1	SAE 15W-50	1
SAE 20W-50	1	SAE 20W-60	1
SAE 40	1	SAE 50	1

SPECIFICATIONS · SAE 5W-40

- API SN/CF
- ACEA C3
- FIAT 9.55535 S2
- FIAT 9.55535 GH2
- FORD 917 A / WSS M2C 917A
- MB 229.31
- MB 229.51
- MB 229.52
- MB 226.5
- BMW LL-04
- PORSCHE C40
- VW 505.00
- VW 505.01
- VW 511.00
- GM DEXOS-2
- RENAULT RN 0700
- RENAULT RN 0710

Synthetic Lubricant for Petrol & Diesel Engines with FAP/DPF or GPF Filters

Synthetic SAE 5W-40 for compatible petrol and diesel engines with FAP/DPF or GPF particulate filters, where its use is specified. The registered formulation focuses on thermo-oxidative stability and protection of mechanical operation.

KEY ADVANTAGES

- High thermal and oxidative resistance
- High lubricating film strength
- Resistance to viscosity thickening
- Low pour point and very high viscosity index for protection even under extreme temperature changes
- Anti-corrosion, anti-rust and cleaning properties

PACK	CODE	UNITS / BOX	PER PALLET
1 L	GDEK12301	18	54 boxes
4 L	GDEK12344	4	60 boxes
5 L	GDEK12305	4	50 boxes
20 L	GDEK12320	—	48 units
60 L	GDEK12360	—	18 units
208 L	GDEK123208	—	4 units
1.000 L	GDEK1231000	—	1 unit

ZENTROX

PASSENGER CARS & VANS

TURION 5W-40 C3

TYPICAL CHARACTERISTICS

Property	Unit	Method	Typical value
Colour	-	Visual	Amber
Appearance	-	Visual	Limpid
Density	kg/dm ³	ASTM D7042	0,857
Kinematic viscosity at 40°C	cSt	ASTM D445	91,0
Kinematic viscosity at 100°C	cSt	ASTM D445	15,02
Viscosity Index	-	ASTM D2270	174
Flash Point	°C	ASTM D92	229
Freezing point	°C	ASTM D97	-38

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.