

GEARTRON

GEAR OILS

ZENTRIS 75W-90



GEARTRON RANGE

9 products · 6 grades

SAE 75W	1	SAE 75W-80	2
SAE 75W-90	2	SAE 75W-140	1
SAE 80W-90	2	SAE 85W-90	1

SPECIFICATIONS · SAE 75W-90

- API GL-4, GL-5 MT-1
- MAN 341 Z2 TYPE E2 / E3
- MAN 342 M3
- MB 235.0
- MB 235.8
- MB 235.11
- BMW MTF LT1-4
- SCANIA STO 1:0
- MACK GO-J
- VOLVO 97310
- VW G50/G51
- ZFTE ML 05A/07A/08/12B/16F/21A

Multipurpose Synthetic Gear Lubricant for Gearboxes & Integrated Differentials

Synthetic multi-purpose SAE 75W-90 for compatible manual and synchronized gearboxes, integrated differentials and selected transmissions. Intended for applications requiring API GL-4/GL-5, aimed at protection under mechanical load.

KEY ADVANTAGES

- Very high thermal and oxidative stability
- Maximum durability of mechanical components
- Exceptional friction control
- Maximum resistance to wear
- Maximum compatibility with materials used in these systems

PACK	CODE	UNITS / BOX	PER PALLET
1 L	GDEK50901	18	54 boxes
4 L	GDEK50944	4	60 boxes
20 L	GDEK50920	—	48 units
60 L	GDEK50960	—	18 units
208 L	GDEK509208	—	4 units

GEARTRON

GEAR OILS

ZENTRIS 75W-90

TYPICAL CHARACTERISTICS

Property	Unit	Method	Typical value
Colour	-	Visual	Amber
Appearance	-	Visual	Limpid
Density	kg/dm ³	ASTM D7042	0,858
Kinematic viscosity at 40°C	cSt	ASTM D445	98
Kinematic viscosity at 100°C	cSt	ASTM D445	16,2
Viscosity Index	-	ASTM D2270	178
Flash Point	°C	ASTM D92	226
Pour Point	°C	ASTM D97	-47

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.